

Exec-SearchPath-01

Path-searching Exec functions are susceptible to malicious programs inserted into the search path

Sean Barnum, Cigital, Inc. [vita¹]

Copyright © 2007 Cigital, Inc.

2007-03-22

Part "Original Cigital Coding Rule in XML"

Mime-type: text/xml, size: 8329 bytes

Attack Category	<ul style="list-style-type: none">• Path spoofing or confusion problem• Malicious Input																	
Vulnerability Category	<ul style="list-style-type: none">• Indeterminate File/Path• Process management																	
Software Context	<ul style="list-style-type: none">• Process Management																	
Location																		
Description	<p>Path-searching Exec functions are susceptible to malicious programs inserted into the search path.</p> <p>The APIs execlp, execvp, popen, and system are usually implemented through a shell or exhibit shell-like characteristics. If user input can affect the arguments to the function a malicious user could change or add commands to be run.</p> <p>These functions search the path if a full path to the program is not specified. When using these functions always specify the full path to the program. The Windows _exec and system family of functions is also vulnerable in the same manner. Also be sure to include the file extension (.exe, .com, .bat) to prevent unwanted matches.</p>																	
APIs	<table><tr><th>Function Name</th><th>Comments</th></tr><tr><td>_execl</td><td></td></tr><tr><td>_execle</td><td></td></tr><tr><td>_execlp</td><td></td></tr><tr><td>_execlpe</td><td></td></tr><tr><td>_execv</td><td></td></tr><tr><td>_execvp</td><td></td></tr><tr><td>_execvpe</td><td></td></tr></table>		Function Name	Comments	_execl		_execle		_execlp		_execlpe		_execv		_execvp		_execvpe	
Function Name	Comments																	
_execl																		
_execle																		
_execlp																		
_execlpe																		
_execv																		
_execvp																		
_execvpe																		

1. <http://buildsecurityin.us-cert.gov/bsi-rules/35-BSI.html> (Barnum, Sean)

_spawnl	
_spawnle	
_spawnlp	
_spawnlpe	
_spawnv	
_spawnve	
_spawnvp	
_spawnvpe	
_texecl	
_texecle	
_texeclp	
_texeclpe	
_texecv	
_texecve	
_texecvp	
_texecvpe	
_tspawnl	
_tspawnle	
_tspawnlp	
_tspawnlpe	
_tspawnv	
_tspawnve	
_tspawnvp	
_tspawnvpe	
_wexecl	
_wexecle	
_wexeclp	
_wexeclpe	

	_wexecv							
	_wexecve							
	_wexecvp							
	_wexecvpe							
	_wspawnl							
	_wspawnle							
	_wspawnlp							
	_wspawnlp							
	_wspawnlpe							
	_wspawnv							
	_wspawnve							
	_wspawnvp							
	_wspawnvpe							
	_wsystem							
	execlp							
	exec							
	execvp							
	popen							
	system							
Method of Attack	<p>These functions will search the path for the first match to the specified program and are thus susceptible to path spoofing attacks. Additionally, on Windows platforms, these functions will execute a .com program before a .exe program unless the file extension is fully specified. This could allow an attacker to place a malicious .com program in the same location as a similar .exe program.</p>							
Exception Criteria								
Solutions	<table> <tr> <th>Solution Applicability</th><th>Solution Description</th><th>Solution Efficacy</th></tr> <tr> <td>When any type of path-searching Exec function is used.</td><td>When using these functions always specify the full path to the program.</td><td>Effective.</td></tr> </table>	Solution Applicability	Solution Description	Solution Efficacy	When any type of path-searching Exec function is used.	When using these functions always specify the full path to the program.	Effective.	
Solution Applicability	Solution Description	Solution Efficacy						
When any type of path-searching Exec function is used.	When using these functions always specify the full path to the program.	Effective.						

		Also be sure to include the file extension (.exe, .com, .bat) on Windows platforms to prevent unwanted searches.	
Signature Details	Any of the indicated APIs, with a non-absolute path or (on Windows) no explicit file extension.		
Examples of Incorrect Code	system("MyProgram");		
Examples of Corrected Code	system("/usr/local/bin/MyProgram");		
Source References	<ul style="list-style-type: none"> • Viega, John & McGraw, Gary. <i>Building Secure Software: How to Avoid Security Problems the Right Way</i>. Boston, MA: Addison-Wesley Professional, 2001, ISBN: 020172152X, pg. 322 • man pages for execlp, execvp, popen, and system • Microsoft Developer Network Library 		
Recommended Resource			
Discriminant Set	Operating Systems	<ul style="list-style-type: none"> • Windows (All) • UNIX (All) 	
	Language		

Cigital, Inc. Copyright

Copyright © Cigital, Inc. 2005-2007. Cigital retains copyrights to this material.

Permission to reproduce this document and to prepare derivative works from this document for internal use is granted, provided the copyright and “No Warranty” statements are included with all reproductions and derivative works.

For information regarding external or commercial use of copyrighted materials owned by Cigital, including information about “Fair Use,” contact Cigital at copyright@cigital.com¹.

The Build Security In (BSI) portal is sponsored by the U.S. Department of Homeland Security (DHS), National Cyber Security Division. The Software Engineering Institute (SEI) develops and operates BSI. DHS funding supports the publishing of all site content.

1. <mailto:copyright@cigital.com>